



DRUID E

TECHNICAL SPECIFICATIONS

DRUID E

TECHNICAL SPECIFICATIONS



FORK LENGTH (MAX.)	586mm
RECOMMENDED FORK OFFSET	44mm
SHOCK LENGTH (EYE - EYE)	210mm
SHOCK STROKE	55mm
SHOCK HARDWARE (BOTH ENDS)	30x8mm
HEAD TUBE DIAMETER UPPER	44mm
HEAD TUBE DIAMETER LOWER	55.95mm
S.H.I.S.	ZS44/28.6 ZS56/40
REAR DROPOUT SPACING (O.L.D.)	148mm
REAR AXLE SPECIFICATION	L180mm / TL 20mm / TP M12 x 1.00
BOTTOM BRACKET	N/A
CHAIN LINE (CL)	55mm
MAX. CHAIN RING*	S1: 36T S2: 36T S3: 38T S4: 38T
CHAIN LENGTHS*	S1: 120 L S2: 122 L S3: 124 L S4: 126 L
SEATPOST DIAMETER	31.6mm
MAX. SEATPOST INSERTION *	S1: 260mm S2: 275mm S3: 300mm S4: 320mm
SEAT CLAMP DIAMETER	34.9mm (Included)
BRAKE MOUNT	200mm Post Mount
ISCG 05	N/A
RECOMMENDED TIRE SIZE	27.5 x 2.5
MAX. TIRE SIZE	27.5 x 2.6
MAIN PIVOT BEARINGS	6903 MAX (17mm x 30mm x 7mm) QTY: 2
FRONT TRIANGLE BEARINGS	6903 MAX (17mm x 30mm x 7mm) QTY: 2
ROCKER LINK BEARINGS	6901 MAX (12mm x 24mm x 6mm) QTY: 2
HORST LINK PIVOT BEARINGS	6901 MAX (12mm x 24mm x 6mm) QTY: 4
IDLER PULLEY BEARING	6903 MAX BOSL (17mm x 30mm x 7mm) QTY: 2

*PER FRAME SIZE