

TECH SPECS

FORK LENGTH (MAX.)	544mm	SEAT POST DIAMETER	31.6mm
RECOMENDED FORK OFFSET	44mm	MAX. SEAT POST INSERTION *	S1: 220mm S2: 240mm S3: 270mm S4: 310mm
SHOCK LENGTH (EYE - EYE)	190mm	SEAT CLAMP DIAMETER	34.9mm (Included)
SHOCK STROKE	45mm	BRAKE MOUNT	180mm Post Mount
SHOCK HARDWARE (BOTH ENDS)	30x8mm	ISCG 05	Tabs for chain guide only
HEAD TUBE DIAMETER UPPER	44mm	RECOMMENDED TIRE SIZE	29 x 2.4
HEAD TUBE DIAMETER LOWER	55.95mm	MAX. TIRE SIZE	29 x 2.6
S.H.I.S.	ZS44/28.6 ZS56/40	MAIN PIVOT BEARINGS	6903 Max (17mm x 30mm x 7mm) QTY: 2
REAR DROPOUT SPACING (O.L.D.)	148mm		6903 Max (17mm x 30mm x 7mm) QTY: 2
REAR AXLE SPECIFICATION	L180mm / TL 20mm / TP M12 x 1.00	LINKAGE PIVOT BEARINGS	6901 Max (12mm x 24mm x 6mm) QTY: 2
BOTTOM BRACKET	73mm BSA Threaded	HORST LINK PIVOT BEARINGS	6901 Max (12mm x 24mm x 6mm) QTY: 4
CHAIN LINE (CL)	55mm	FRAME WEIGHT (without shock)	2.27Kg
MAX. CHAIN RING*	S1: 32T S2: 34T S3: 36T S4: 38T		
CHAIN LENGTHS*	S1: 114 S2: 116 S3: 118 S4: 120		
	S1: 116 S2: 118 S3: 120 S4: 122		

*PER FRAME SIZE